



# BlueAg™

## HEAVY DUTY DIESEL MOTOR OIL SAE 15W-40

### DESCRIPTION:

BlueAg™ Heavy Duty Diesel Motor Oil provides significant oil film protection to moving parts, resists viscosity breakdown from shearing action and thermal oxidation. Exceeds high temperature performance demands in the latest line of diesel engines.

Recommended for low-emission diesel and turbo-diesel engines equipped with EGR (Exhaust Gas Recirculation), Diesel Particulate Filters and SCR (Selective Catalytic Reduction) systems. Suitable for use in gasoline engines.

### BENEFITS:

- Oxidation Control & Corrosion Prevention - contains hi-temp, dual function anti-oxidant and anti-corrosion chemistry to resist oil breakdown and acid formation
- Deposit Control - outstanding piston and cylinder deposit control surpasses industry performance standards
- Improved Oil Aeration Control - improves ability to lubricate parts, mitigate oil flow cavitation and control oxidation effectively.

### APPLICATION:

#### APPROVED:

- API CK4/SN
- ACEA E9-2012, E7

#### MEETS PERFORMANCE SPECIFICATIONS:

- API CJ-4, CI-4 PLUS, CI-4, CH-4/SN, SM, SL, SJ
- CATERPILLAR ECF-3, ECF-2
- CUMMINS CES 20086, CES 20081
- DAIMLER MB 228.31
- DETROIT DIESEL DFS 93K222, 93K218
- MACK/VOLVO E0S-4.5, EO-O Premium Plus, EO-O, VDS 4.5, VDS-4, VDS-3
- MAN M3575
- MTU CATEGORY 2.1
- RENAULT RLD-4, RLD-3

### PRODUCT INFORMATION:

Typical Properties	15W-40 CK-4/SN	Part No.	SKU Description	UPC Code
Viscosity @ 40°C, cSt	118.5	BAG4MK50	BULK	---
Viscosity @ 100°C, cSt	15.7	BAG4MK5330	330 GAL TOTE	0-74804-06760-6
Viscosity Index	141	BAG4MK51	55 GAL DRUM	0-74804-06759-0
Pour Point, °C	-33			
Flash Point, °C	236			
Sulfated Ash wt%	0.98			
TBN	9.6			



Old World Industries, LLC  
Northbrook, IL 60062 • 800-323-5440  
BlueAgSolutions.com

©2018 Old World Industries, LLC. All Rights Reserved. PEAK, PEAK G Mountain Graphic, BLUEAG and BLUEAG G Drop Graphic are trademarks of Old World Industries, LLC. API American Petroleum Institute Certified Diesel Exhaust Fluid Design is a registered trademark of the American Petroleum Institute Corporation.